



CONTAR COVING SYSTEM

Contar Coving System is made from technically advanced methyl methacrylate resin. It is a thixotropic resin that is trowel applied and can be used to form coving as part of a seamless resin floor system. It can be coloured to closely match existing floor colours.

FIELDS OF APPLICATION

Contar Cove mix is ideal for finishing off resin flooring systems where a seamless decorative / practical edging detail is required. Within the food industry coving is recommended for any area where regular wash downs occur.

- ◆ Food manufacturing
- ◆ Hospitals
- ◆ Food preparation areas
- ◆ Warehouses
- ◆ Walkways Finishing
- ◆ Wet rooms

SYSTEM FEATURES & BENEFITS

- ◆ Highly flexible resistant to cracking
- ◆ UV resistant
- ◆ Hygienic and easy to clean
- ◆ Rapid installation time

SUBSTRATE REQUIREMENT

Substrate must be dry, free from laitance, dust and other contaminations. Check the relative humidity at ground level and always use the correct Contar substrate primer prior to applying the Contar Coving System. Please contact Contar Resins technical team for further advice.

Tel: 01277843955

E-Mail: info@contarresins.co.uk

MODEL SPECIFICATION

Product:	Contar Cove System
Finish:	Textured (depending on client specification)
Thickness:	6mm upwards
Colour:	Client specification/ choice
Manufacturer:	Contar Resins Ltd
Preparatory work and application in accordance with the manufactures instructions.	

SYSTEM OVERVIEW

Contar Primer
Contar Cove Mix Resin
Contar Coloured Quartz
Contar Sealer

INSTALLATION SERVICES

The installation should only be carried out by a Contar approved contractor. Obtain details of the Contar approved contractors by contacting Contar Resins Ltd or via our web site at www.contarresins.co.uk

CHEMICAL RESISTANCE

Please contact Contar technical department for information.

Contar Resins Ltd
The Coach House
West Hanningford Road
Baddow Park, Chelmsford
Essex, CM2 7SY
01227 843955
info@contarresins.co.uk
www.contarresins.co.uk

Registered Address:
Monometer House, Rectory Grove,
Leigh On Sea, Essex, SS9 2HL

VAT No: 213 5000 73
CRN No: 0956 3006

Speed of cure*

Pot Life 10-20 mins*

Finish curing to full specification-1 hour

**Pot life & curing times will be dependant of substrate and air temperature.*

Different curing times can be achieved by altering the amount of BPO used within the temperatures of 0°C--30°C. For temperatures outside of this range then please contact Contar Resin Technical support.

Caution Contar materials have a characteristic odour during application which is nontoxic and non-injurious to health. Ensure all open food is covered and adequate ventilation is available. See material safety data sheet for full information or contact Contar technical dept.

Aftercare and Maintenance

Clean regularly using a mop or cloth in conjunction with a mildly alkaline detergent


Mixing & Application

Refer to Contar Resins Ltd installation guide.

DECORATIVE QUARTZ STANDARD COLOUR RANGE



ASH



BLIZZARD



MAGNET



DOVE



MAESTRO




JADE



HARBOUR



WINE



CLOWN



BEACH



TIMBER



MAIZE

NOTE:

Contar Resins Ltd endeavors to ensure that all information and advice given is accurate and correct. However, the company cannot take responsibility for the selection of products for specific applications. Therefore, any prospective customers should satisfy themselves that the product is suitable for the environment in which it will be installed.

Accordingly, Contar cannot take responsibility for the selection of a product unsuitable for the application. The information detailed in this communication is liable to change without prior notification. All resin floors are hand applied resulting in a surface texture that can vary.

Contar Resins Ltd, The Coach House,
West Hanningford Road, Baddow Park,
Chelmsford, Essex, CM2 7SY

01227 843955 info@contarresins.co.uk
www.contarresins.co.uk

Registered Address: Monometer House,
Rectory Grove, Leigh On Sea, Essex, SS9 2HL
VAT No: 213 5000 73 CRN No: 0956 3006